


単位：mm

# ホースニップル・HN

※SS寸法です。SUSは別表




SS41



SUS304

呼び径	A	B	肉厚
12	55	12.7	1.0
15	60	16	1.0
19	65	21	1.0
25	70	25.4	1.0
32	100	31.5	1.2
38	100	38	1.2
50	120	50.8	1.6
65	145	63.5	2.0
75	160	76.3	2.0
100	210	101.6	2.5
125	220	125	3.2
150	245	150.2	3.2
200	300	204	4.2
250	400	252	3.2
300	480	303	6

# ラッパ竹の子



SS41




SUS304

呼び径	A	B	C	肉厚
19	21.7	80.0	27.2	2.3
25	27.0	85.2	34.0	3.0
32	31.4	100	42.7	3.0
38	40.2	124.0	48.6	//
50	51.9	130.0	60.5	//
65	64.7	138.0	76.3	//
75	77.1	153.0	89.1	3.5
100	101.6	168.0	114.3	4.0
125	126.4	186.0	139.8	//
150	152.6	199.0	165.2	//
200	203.0	240.0	216.3	//
250	254.0	330.0	267.4	5

参考寸法：SS41・SUS304共寸法図は別途ご参照下さい。


# 雄ネジ竹の子・OT、Fc・PP (材質)



呼び径	A	B	C	PT
19	61	21	38	3/4
25	68	26	38	1
32	70	33	45	1 1/4
38	78	38	50	1 1/2
50	90	52	60	2
65	109	65	72	2 1/2
75	118	77	85	3
100	144	103	104	4
125	171	127	129	5
150	188	149	140	6

※寸法表はFC材質用ですが変わる事もあります。

# ホースカップリング(ガス山)・HC



垂鉛ダイカスト




B.S.

呼び径	A	B	C	重量g
12	68	13	40	70
19	72	19	45	100
25	84	25	57	200
32	105	33	69	220
38	115	38	78	430
50	139	50	98	800
65	177	64	110	1,250
75	200	75	138	1,770
100	240	100	170	3,800
150	340	150	230	10,800

材質・①真鍮 ②垂鉛 ③アルミ ⑤SUS304


# ハンドル付(メス)



呼び径	A	B	重量	
			真鍮	アルミ
38	62	105		
50	76	137	360	170
65	99	198	870	300
75	103	215	1,700	430
100	132	280	2,100	720


※寸法表はFC材質用ですが変わる時もあります。

# 散水ノーズル(A&)



竹の子径	A	B
3/4	112	21
1	138	27
1 1/4	157	33
1 1/2	157	38
2"	155	51

# 町野式接手(差込接手)・Bs



BC製




軽合金製

ステンレス製もあります。

呼び径	A	B	C	D	E	F	G	H	I	M	g	M		g	
												BC	AL	BC	AL
19	89	19	15	21	40	5	45	22	52	BS	180	//	//	230	
25	94	25	20	21.5	45	7	62	29	52	BS	250	//	//	315	
32	120	31	24	27	63	5	77	35	66	BS	580	//	//	460	
38	125	38	32	28	75	7	80	43.6	70	BC	700	//	//	640	275
50	157	51	44.5	35	92	8	100	55.6	90	BC	1250	//	//	1K	560
65	181	63.5	57	39	110	9	120	68.5	106	BC	1980	//	//	2K	750
75	230	76	68	45	123	10	140	81.3	127	BC	3300	//	//	3.5K	
100	281	101	92	45	155	14	172	108	147	BC	6860	//	//	6.5K	

## 鉄板製ストレーナー・ST




呼び径	A	B	D	F×n	L
19	85	70	19.0	6×5	120
25	85	75	25.4	6.5×5	130
32	127	70	31.8	7.5×5	145
38	135	75	38.1	8×5	150
50	135	75	50.8	8×5	150
65	165	100	63.5	12×5	210
75	165	100	76.2	11×5	210
100	190	95	101.6	12×5	220
125	215	115	127.0	16×5	245
150	225	190	152.4	19×7	350

## 捻子付ストレーナー・ST2




呼び径	A	B	C	D
19	87	65	75	3/4
25	87	65	75	1
32	127	65	75	1 1/4
38	127	65	75	1 1/2
50	127	65	75	2
65	168	90	100	2 1/2
75	168	90	100	3
100	194	90	100	4
125	214	102	115	5
150	250	146	163	6

## フードバルブ・FV




呼び径	A	B	重量g
19	100	98	
25	106	110	
32	118	116	
38	149	141	2,230
50	151	144	2,500
65	179	157	3,470
75	195	165	3,800
100	250	235	8,800
125			
150	330	285	16,800

## 籐カゴ・FS



呼び径	A	B
100	150	115
125	175	140
150	220	160
200	250	310
250	285	255
300	365	310
350	385	350
400	440	400
450	495	450
500	550	500

## L型ホースニップル・LHN




呼び径	A	B
38	120	38.6
50	135	50.8
65	150	63.5
75	165	76.3
100	232	101.6
150	320	152.2
200	408	204

## U型ホースニップル・UHN



呼び径	A	B	C
50	160	200	50
65	190	233	63
75	230	260	75
100	305	320	100
150	460	420	150
200	610	550	200

## 異径ホースニップル



呼び径	A	B	C
2"×1 1/2"	50.8	39	320
2 1/2"×2"	63.5	50.8	350
3"×2 1/2"	76.3	63.1	370
4"×3"	101.6	76.3	420
6"×5"	152	101.6	500
8"×6"	204	152	590

サイズにより多少形状が異なる事もあります。

## T型ホースニップル・THN



サイズ	A	B
38		
50		
65		
75		
100		
125		
150		
200		

詳細はお問い合わせ下さい。

低圧用・高圧用タイプ有ります。